

Technical data sheet

Composition:	Topcoat: Vinyl
Backing:	Backing 100% Polyester
Weight:	635 gr/m ²
Width:	min. 137cm
Roll size:	+/- 30m*
Abrasion:	> 100.000 cycles (MARTINDALE)
Cold Crack:	-29° C
UV-Resistance:	ISO 105 B02: ≥7/8 (Blue Wool Scale) ISO 105 B04: ≥4/5 (Grey Scale)

* Typical roll length. Length may vary depending on the availability of standard roll size

Flame Retardancy**:	EU EN 1021 Part 1 & 2 EU IMO 2010 FTP Part 8 DE DIN 4102 B2 US FMVSS302 US UFAC Fabric - Class I US NFPA 260 Class I
Other characteristics	EU (MED) Marine Equipment Directive UK UKCA

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behaviour of this or any other material under actual conditions.

FINISHES AND TREATMENTS



Antimicrobial:	Waterproof Mildew Resistant Backing and Face Antifungal Protection Antibacterial Protection Antimycotic Protection
-----------------------	--

*** Testing was conducted with material exposed to Staphylococcus aureus, Staphylococcus aureus (MRSA), Escherichia coli and Klebsiella pneumoniae.

WARRANTY 5 Years. Terms and Conditions apply.

PERMABLOK³ and SPRADLING[®], are registered trademarks of Spradling Holdings, Inc[®].




SUSTAINABLE PRODUCT PROFILE

Attributes

PHTHALATE FREE

Heavy Metal Free



*In accordance with REACH, RoHs and ECHA regulations

- AZO = Azo dyes
- CFC = Chlorofluorocarbons
- HCFC = Hydrochlorofluorocarbons
- BPA = Bisphenol A
- PBTs = Persistent Bio accumulative and Toxic Chemicals
- PCP = Pentachlorophenol
- PCB = Pentachlorinated Biphenyl
- PCT = Polychlorinated Terphenyls

Certifications



Sustainable manufacturing certifications



Compliances

